STRAIGHT RUNNING CHAINS
HEAVY DUTY SINGLE HINGE WITH HIGH FRICTION SURFACE

8257 VG









Characteristics:
- The return section of the conveyor can be constructed using standard wearstrips or return rollers to support the chain on its return.

Advantages:
- High strength
- Helps standardising your conveyor constructions
- Same hinge width available in many chain types, both steel and plastic, also LBP chains and Flat Top chains

Pin material: Austenitic Steel

MATERIAL Pages 4⇨7
Pages 296⇨298
Pages 333⇨337

Chain - Ref.	Code	Material		Breaking load N	Width L		Width WR		Weight Kg/m
		Plate	Rubber		mm	inch	mm	inch	
NGD 8257 K450 VG	**11086**	**NGD** Dark Grey	**TPR** Water blue 70 shore A	9.000	114.3	4 ½	90	3 ½	1.95
NGD 8257 K750 VG	**11083**				190.5	7 ½	134	5 5⁄16	2.25
NGD 8257 K1000 VG	**11084**				254.0	10	192	7 ½	2.60
NGD 8257 K1200 VG	**11085**				304.8	12	252	10	2.95

Standard length: 80 pitches (10 ft. - 3.048 m)

Breaking Load according to Standard ISO 4348 - DIN 8153