

Product guides

GUIDE RAILS

Material:

- Metal profile in anodized aluminium.
- Extruded profile in UHMWPE.

Characteristics:

- Very low friction coefficient.
- High resistance to chemical agents.

Notes: Aluminium profile and plastic profile are supplied assembled.

Application: as side guides for air conveyor and standard conveyor.



Polyethylene




Anodized aluminium



Accessories



Consult pages
105 → 107 for
bending machines




ALUMINIUM PROFILE

Supply: 3 or 6 meters.

Packaging: 30 meters.

Code	Length	Weight Kg/m
19094	3 m	0.50
19094L	6 m	0.50




GUIDE RAILS

Supply: 3 or 6 meters.

Packaging: 30 meters.

Code	Colour	Length	Weight Kg/m
190360N	Black	3 m	0.59
190360NL	Black	6 m	0.59
190360P	Yellow	3 m	0.59
190360PL	Yellow	6 m	0.59
190360	Orange	3 m	0.59
190360L	Orange	6 m	0.59
190360W	White	3 m	0.59
190360WL	White	6 m	0.59



EXTRUDED PROFILE

Supply: coils.

Packaging: 60 meters.

Code	Colour	Weight Kg/m
19068N	Black	0.09
19068P	Yellow	0.09
19068	Orange	0.09
19068W	White	0.09

