

Product guides

STANDARD GUIDE RAILS

Material:

- Metal profile, see the table.
- Plastic profile in UHMWPE.

Characteristics:

- Very low friction coefficient.
- Moderate resistance to chemical agents.
- No liquid absorption.

Supply:

- 3 or 6 meters.



304 Stainless steel



Polyethylene




Zinc plated steel



Accessories



Consult pages
105 → 107 for
bending machines




METAL PROFILE

Supply: 3 or 6 meters.

Packaging: 30 meters.

Code	Metal profile material	Length	Weight Kg/m
16450	S/S AISI 304	3 m	0.40
16450L		6 m	0.40
16449	Zinc plated steel	3 m	0.40
16449L		6 m	0.40




EXTRUDED PROFILE

Supply: 3 or 6 meters.

Packaging: 30 meters.

Code	Colour of guide	Length	Weight Kg/m
19083	Green	3 m	0.28
19083L	Green	6 m	0.28
19084	Black	3 m	0.28
19084L	Black	6 m	0.28



STANDARD GUIDE RAILS

Supply: 3 or 6 meters.

Packaging: 30 meters.

Notes: the metal profile and plastic profile are supplied assembled.

Code	Colour of guide	Metal profile material	Weight Kg/m
19035	Green	S/S AISI 304	0.68
19035L	Green		0.68
19036	Black		0.68
19036L	Black	Zinc plated steel	0.68
19046	Green		0.68
19046L	Green		0.68
19047	Black		0.68
19047L	Black		0.68