

**Characteristics:**

- The chains series 881 M and 8857 M are securely retained in the curve by magnets located under the hinge of the chain in the upper part of curve. As there are no TAB or BEVEL shoes on these chains they can be easily removed from the curve for maintenance or for cleaning, without dismantling the chain.
- The enlarged surface of our 881 MO series offers improved product support compared to the 881 M series.

Advantages:

- Optimum flatness of chains in curves
- Less power consumption
- For high speed lines
- Best product transfer along as well as across the running direction

On request and for adequate quantities these chains can be produced in:

C45

Through Hardened
Carbon Steel

Note:

Pin in Ferritic Stainless Steel.



Pages
4⇒7



Pages
196⇒214



Page
260



Pages
266⇒270



Pages
333⇒337

Chain - Ref.	Code	Material	Flatness (max) mm	Polished hinges	Max. working load	Finish µm	Width L		R min.	SC	Weight Kg/m
							mm	inch			
SS 881 MO K325	10208	STANDARD	0.15	yes	5.400	0.6	82.5	3 ¼	500	45	2.60
SS 881 MO K330	10209		83.8				3 ⅞	2.65			
SS 881 M K450	10211		114.3				4 ½	457	3.10		
SS 881 M K750	10212		190.5				7 ½		4.90		
SSE 881 MO K325	10206	EXTRA PLUS	0.15		6.000	0.3	82.5	3 ¼	500		2.60
SSE 881 MO K330	10207		83.8				3 ⅞	2.65			
SSE 881 M K450	10201		114.3				4 ½	457	3.10		
SSE 881 M K750	10203		190.5				7 ½		4.90		
SSE 881 MO K325 HB	10213	EXTRA PLUS HB	0.15		6.000	0.3	82.5	3 ¼	500		2.60
SSE 881 MO K330 HB	10214						83.8	3 ⅞			2.65

Standard length: 80 pitches (10 ft. - 3.048 m)

Breaking Load according to Standard ISO 4348 - DIN 8153